

# OASIS NETWORK VISION ANNUNCIATOR

OVC00NC-10 (Red), OVC00NC-40 (Gray), and OVC00NC-60 (Black)



**MADE IN  
BRITAIN**

## Product Overview

The Oasis Network Vision Annunciator is the most qualified annunciator on the market. It is a full-color graphical display and touchscreen. It represents the most versatile annunciator for life safety systems available today. The Annunciator is a full-function fire alarm repeater that is configurable and application-flexible for use in applications such as hospital nursing stations and elevator alarms.

Oasis Network Vision Annunciators can be configured to fully replicate fire control panel functionality, or to operate as simple, display-only devices for applications where access to fire alarm controls are inappropriate.

## Standard Features

- Full-color 7" (800 x 480 pixel) interface
- Replicates information displayed at the FACP
- Automatic display brightness adjustment
- Internal buzzer
- Connects via control panel network terminals
- Low current, 24V DC powered
- Configurable functionality
- Enable key-switch
- Sheet steel enclosure
- Surface or semi-flush enclosure options available

## Technical Specifications

<b>Supply Voltage</b>	21 - 30VDC
<b>Quiescent Current</b>	216mA typical (buzzer off @ 24V DC)
<b>during Power Failure</b>	246mA typical (buzzer on @ 24V DC) 341mA max (buzzer on @ 21V DC)
<b>Maximum Number of Units on a Network</b>	31 Annunciators
<b>Size</b>	9.25" x 6.7" x 2.2" (235 mm x 170 mm x 55 mm)
<b>Display</b>	Full color 800 x 480 LCD with resistive touch screen and automatic back-light dimming
<b>Construction</b>	18 AWG, 1.2 mm mild sheet steel
<b>Cable Entry</b>	2 x 20 mm knockouts on top & bottom 4 x 20 mm and 2 x 28 mm knockouts in back
<b>Vision Annunciator Electronics Only</b>	S787
<b>Finish</b>	Epoxy Powder Coated
<b>Color</b>	<ul style="list-style-type: none"> <li>● Red (RAL3002)</li> <li>● Gray (BS 00 A 05)</li> <li>● Black (RAL9005)</li> </ul>
<b>Optional Semi-Flush Mounting Collar Kit</b>	KM1098RD - Red KM1098GY - Gray KM1098BS - Black
<b>Weight</b>	4.4 lbs (2 kg) maximum
<b>IP Rating</b>	IP30