UL Product iQ®

Wet-chemical-solution Extinguishing System Units

COMPANY

Avenger Systems LLC
11586 Zagarolo Lane
Las Vegas, NV 89141 United States

EX28006

Trademark and/or Tradename: "Avenger K or Avenger FLEX"
Note: For additional marking information, refer to the Guide Information Page.

Stored-pressure wet chemical solution extinguishing system units, Model(s): 250

Stored-pressure wet chemical solution extinguishing system units, Model(s): Avenger Series Models 275 (p/n 24542) 2.75 gal., 375 (p/n 24543) 3.75 gal., 475 (p/n24544) 4.80 gal. and 675 (p/n 24545) 6.14 gal. The units are designed to discharge wet chemical solution from fixed nozzles for the extinguishment of fires occurring in restaurant hoods, plenums, filters, ducts and associated cooking appliances. For temperatures +32° to +120° F (0° to 48.8°C). Operated by automatic means with manual back up. Includes the protection of deep fat fryers, griddles, range tops, woks, upright broilers, electric charbroilers, rock charbroilers, natural charcoal charbroilers, mesquite wood charbroilers and gas radiant charbroilers. A description of the extinguishing system units and the design and installation limitations are contained in the Listee's Installation Manual (p/n AS-18-706) Rev. 1.05 dated January 2019. Copies are available from the Listee.

Last Updated on 2025-02-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."